

## VIBRATING SPIRAL CONVEYOR

Material can be upward transportation, can also be transmitted downward.

SY series vibrating spiral conveyor is a new type vibrating conveyor, SY type vibration conveyor is lifting in the material at the same time, also can complete drying and cooling of the material. Separate groove, and enclosed two kinds of structure, and can according to different technical requirements, design and material particle classification, design inflammable and explosive materials special vibrating conveyor.


- **♦**Equipment covers an area of an area small, easy to production process arrangement.
- **♦**Low noise, simple structure, Installation, maintenance is convenient.
- **♦**Structure simple and reasonable, low energy consumption, save electricity,












### **WORKING PRINCIPLE**

SY Series vibrating spiral conveyor of vibratory motor, installed at the bottom or top of the transmission tower, two vibrating motors symmetric cross installation. Conveyor towers constitute by the pipe body and welding of spiral conveyor trough. Conveyor towers installed in the vibration damping device, vibration damping device is composed of base and vibration isolation spring. When vertical conveyor job, according to the principle of dual vibration motors self-synchronization, produced by the vibration motor excitation force, To force the whole conveyor tower body horizontal circular motion and vertical upward movement, Spiral groove in the material, the role of the conveying groove, a uniform circular motion, throwing down the conveyor tub upward movement, so as to complete material conveying operation up (or down).


# Air outlet water outlet Discharge port Column (Cooling vents can be added) Spiral stainless steel tank (A sealing cover can be added to the outside) 360° feed tray rubber spring Motor Reinforced base

#### **STRUCTURE**





### **FEATURES**





### MODEL AND SPECIFICATIONS

Model	Conveying capacity (t/h)	Material particle size(mm)	Conveyor trough size width times height ( cm )	Conveying distance ( m )	Vibration ( min )	Motor Power ( kw )	Gross weight ( kg )
CZ250	~ 1.0	≤50	25×25	~2.0	960	2×0.4	230
CZ300	~ 1.5	≤50	30×30	~3.0	960	2×0.4	305
CZ400	~ 2.0	≤50	40×30	~5.0	960	2×0.75	580
CZ500	~ 2.5	≤50	50×35	~6.0	960	2×1.5	880
CZ600	~ 3.0	≤50	60×40	~8.0	960	2×2.2	1280
CZ700	~ 3.5	≤50	70×40	~10	960	2×3.0	1850



## PRODUCT DISPLAY











## **INSTALLATION SITE**





#### **APPLICATION**

Chemical Industry

Resin, alkali coating, rubber powder, industrial drugs, traditional Chinese medicine powder rubber particles, cosmetics, aluminum chloride solution, paint, etc.

Food Industry

Sugarpowder, soy starch, steviol glycosides, salt, rice flour, rapeseed, milk powder, soy milk, egg powder, soy sauce, juice, etc.

**Metallurgical Mining** 

Limestone, metal ore, cryolite, kyanite, magnesite, mica, quartz sand, quartzite, dolomite, kaolin, silica, graphite, diabase

**Pollution Treatment** 

Resin, alkali coating, rubber powder, industrial drugs, traditional Chinese medicine powder rubber particles, cosmetics, aluminum chloride solution, paint, etc.






#### THE SERVICES WE CAN PROVIDE

Sanyuantang Machine Co., Ltd. has been engaged in foreign trade export for more than 10 years. Its rich export experience ensures that you have worry-free purchasing.

When you cooperate with us, you can enjoy:

- ① Timely response through various communication tools.
- 2 Professional technical guidance to choose the most suitable product for you.
- 3 Economical transportation scheme to cut down transportation cost.
- 4) Thoughful after-sales tracking service from the installation to the daily maintanence.





Xinxiang Sanyuantang Machine Co., Ltd.

website:www.vibrationsieve.com

Add:No.811, Qingnian Road, Qiliying Town,Xinxiang County,

Henan Province China.

Email:info@sanyuantang.com

Whatsapp/ Wechat: 0086 18639095165